



## MP-IP-HD-RX

### HDMI over IP/PoE Receiver



All Rights Reserved

Version: MP-IP-HD-RX\_20251029

## 1. Product Introduction

The MP-IP-HD-RX is a receiver, which designs to match with MP-IP-HD-TX, the units are HDMI over IP power by PoE. It supports receive 1080P 60Hz video, HDCP1.4 compliant. It support power by PoE or DC5V power supply for field using; It provides HDMI transmission up to 150 meters for 1080p video over single CAT6 cable.

### 1.1 Features

- Two power supply PoE or DC 5V;
- Max 150m transmission distance @1080P video.
- IR control.

### 1.2 Package List

- 1x MP-IP-HD-RX unit
- 1x USB-A to USB-C power cable, 0.5M length
- 1x User Manual

*Note: Please contact your distributor immediately if*

*any damage or defect in the components is found*

## 2. Panel Description

### 2.1 Right Panel



① **DISPLAY:** HDMI port to connect HDMI Display to output video.

### 2.2 Left Panel



① **RJ45:** support PoE power supply and connect with switcher to transmit 1080P video max 150m transmission.

② **IR IN:** connect to a IR receiver to control unit;

③ **DC 5V:** connect to a DC 5V power supply to power on the unit.

## 3. Specification

General	
Video Resolution	1080P 60Hz
HDMI Audio Format	LPCM 2ch
Transmission Distance	150m @1080p
HDMI Version	HDMI 1.3a
HDCP Version	HDCP 1.4 compliant.
Delay	10-30ms(Depends Display)
IR Pass	From Rx to Tx
Power Supply	DC 5V 1A
Operation Temperature	-10~55°C
Storage Temperature	-25~70°C
Relative Humidity	30%-85%
Dimensions(W*D*	98 x 69 x 23mm

H)	
----	--