

# Milestone Pro MP-20HDAI-4K

## AI Tracking PTZ Camera

4K Clarity with 20x Optical Precision



**4K**  
30FPS

**20x**  
Optical Zoom

**AI**  
Auto-tracking

**NDI** HX2

Multi  
Network  
Protocols

USB+HDMI  
+RJ45+SDI

Milestone Pro MP-20HDAI-4K is a professional-grade 4K Ultra HD PTZ camera featuring a Sony 8.29MP sensor and 20x optical zoom for crystal-clear imaging in any environment. With advanced AI auto-tracking that maintains perfect framing of presenters, plus smooth PTZ operation, comprehensive I/O options, and multi-protocol support, the 4k camera integrates effortlessly with your workflow. From education and corporate meetings to live streaming and broadcasting, MP-20HDAI-4K offers high-performance video, intelligent automation, and broad compatibility.

# Ultra HD 4K Clarity with 20x Optical Zoom

Equipped with a Sony 1/2.8" CMOS sensor and 8.29 megapixels, Milestone Pro MP-20HDAI-4K ptz camera delivers true 4K clarity with lifelike color fidelity and sharpness. Its 20x Optical Zoom on the other hand effortlessly transitions from wide-angle shots to tight close-ups without losing clarity—perfect for conferencing, live broadcasting, and lecture capture.



## AI-Powered Auto Tracking

Take your production to the next level with intelligent Auto Tracking. MP-20HDAI-4K's built-in AI tracking engine intelligently identifies human targets, adapts to movement, and maintains framing, ensuring presenters remain centered and in focus throughout.



## Precision Engineered Pan-Tilt Control

Featuring industrial-grade motors and ultra-fine stepping, Milestone Pro MP-20HDAI-4K offers exceptionally smooth and quiet pan/tilt performance. Whether executing fast repositioning or slow motion, control with this AI Tracking camera is intuitive and precise. Up to 255 position presets(10 presets by IR remote) allow the camera rapidly switching in any professional setting.



## Rich I/O & Protocols for Flexible Integration

MP-20HDAI-4K supports a comprehensive range of interfaces and streaming protocols, making integration into existing systems effortless.

- Video Outputs: HDMI, USB 3.0, SDI, RJ45(Support PoE+)
- Streaming Protocols: RTSP, RTMP, SRT, NDI®|HX2
- Control Interfaces: RS232, RS485, USB (UVC), IP
- Control Protocols: VISCA, Pelco-D/P, ONVIF, VISCA over IP

Whether for live streaming, remote collaboration, or system integration, Milestone Pro MP-20HDAI-4K adapts to your environment effortlessly.



## Broad Software & System Compatibility

Engineered for modern workflows, MP-20HDAI-4K supports Windows 10/11, macOS 10.10+, Linux, and Android systems with UVC plug-and-play compatibility. From video conferencing platforms to live broadcasting software, this 20x optical zoom AI Tracking 4K ptz camera integrates effortlessly into your preferred setup — no additional drivers needed.

<b>Model No.</b>		MP-20HDAI-4K
Image Sensor		Sony 1/2.8" CMOS
Effective Pixels		8.29MP
Optical Zoom		20x optical zoom
Lens		f=4.95mm~99mm
Aperture		F1.7-F3.7
Horizontal Angle		51.9°~3.0°
Vertical Angle		39.7°~2.2°
Diagonal Angle		63.1°~3.7°
Video Format		HDMI: 4KP@30/25fps, 2KP@60, 1080P@60/59.94/50/30/29.97/25fps, 720P@60/59.94/50/30 3G-SDI: 1080P@60/59.94/50/30/29.97/25fps, 720P@60/59.94/50 USB3.0: H.264: max to 2160P@30fps H.265: max to 2160P@30fps MJPG: max to 2160P@30fps NV12: max to 896P@30fps YUY2: max to 896P@30fps H.264, H.265, MJPG, YUY2
Video Encoding Format		
Backlight Compensation		Support
AI Support		Yes (AI Mode: Auto Framing/Presenter Tracking)
SNR		≥50dB
Focus		Auto / Manual
Digital Noise Reduction		2D & 3D Noise Reduction
Exposure		Auto / Manual
<b>I/O Interface</b>		
Video Interfaces		HDMI, USB3.0, RJ45, SDI
Video Compression Format		H.264, H.265, MJPG, YUY2
LAN		10M/100M adaptive Ethernet port; Support POE IEEE802.3af
Network Protocol		RTSP, RTMP, VISCA over IP, ONVIF, SRT, NDI HX2
Control Protocol		VISCA/Pelco-D/Pelco-P; Baud Rate: 2400/4800/9600/38400
Control Interface		RS232(input only), RS485, USB3.0 (UVC1.1), RJ45
<b>PTZ Parameter</b>		
Horizontal Rotation		350° (±175°) 0.1°/s~100°/s
Vertical Rotation		180° (±90°) 0.1°/s~80°/s
Preset Number		User can set up to 255 presets (10 presets by IR remote)
<b>General Parameter</b>		
Dimension (W*H*D)		166*165*170mm/ 285*217*197mm (before/ after packing)
N.W. / G.W.		1.6kg/ 2.8kg (Net/ Gross weight)

Tel : +912267987577

Email : info@milestonepro.co.in

Address : A-3029/A-3090, 3rd Floor, Bhandup Industrial Estate, L.B.S Marg, Bhandup (W), Mumbai – 400 078, India