

MP-6TX

Wireless HDMI Screen Mirroring Transmitter



PRODUCT OVERVIEW

MP-6TX is a wireless HDMI screen mirroring transmitter for long-distance high-definition signal transmission. It uses 5G-band transmission for strong anti-interference performance and stable operation, with plug-and-play deployment and no network setup required.

KEY FEATURES

- 5G transmission with anti-interference performance for stable wireless operation.
- 1080P/60Hz high-definition picture quality with simultaneous audio and picture transmission.
- Wireless transmission distance up to 40 m under typical unobstructed conditions.
- Supports 1080P, 720P and 480P resolution selection.
- Plug-and-play operation with no network setup required.
- Supports multiple TX units paired with one RX, with switching use.
- Supports image rotation at 90° and 270°.
- Compact design suitable for portable use.

TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Product Model	MP-6TX
Product Type	Wireless HDMI Screen Mirroring Transmitter
HDMI Interface	1 × HDMI input port
Transmission Method	2.4G / 5GHz WiFi
Supported Resolution	1080P/60Hz, 720P/60Hz, 480P/60Hz
Transmission Distance	Typical 40 m without obstruction
Power Supply	DC 5V / 1A
Power Consumption	1 W (Max)
Dimensions (W × H × D)	200 × 65 × 15 mm
Net Weight	33.7 g
Chassis Material	Synthetic Resin

PARAMETER	SPECIFICATION
Operating Temperature	0°C to 50°C (32.0°F to 122.0°F)
Operating Humidity	10% to 90%, non-condensing

INTERFACE & INDICATOR

INTERFACE	FUNCTION
HDMI Input	Connects to the source device.
Pairing Button	Pairing / Disconnect / Reconnect.
LED Indicator	Flashing green: pairing. Steady green: connected with receiver.
USB-C Port	Power input.

PACKAGE CONTENTS

1 × MP-6TX Transmitter | 1 × USB-C to USB-A Power Cable (1 m) | 1 × User Manual

Source: MP-6TX User Manual, Version MP-6TX_2024V1.0. All product specifications and feature descriptions are based on the supplied manual.