

MP-LITE COLLAB

Wireless Conferencing & Presentation Switcher



Product image reproduced directly from the uploaded manual at its original embedded resolution. No crop or artificial product reconstruction used.

Key Features

- 1× HDMI input up to 4K@30Hz and 1× HDMI output up to 4K@60Hz.
- AirPlay, Miracast, Chromecast and WirelessMedia support.
- 2× USB 3.0 Type-A, 1× USB 2.0 Type-A and 1× USB Type-C.
- 2× Gigabit Ethernet; LAN2 supports PoE.
- 3.5 mm analog audio input/output and RS-232 control.
- Up to 4 main windows + 12 thumbnail windows; up to 16 simultaneous connections.

Technical Specifications

Specification	Details
HDMI OUT	1× HDMI 19-pin female; up to 3840×2160@60Hz
HDMI IN	1× HDMI 19-pin female; up to 3840×2160@30Hz
HDCP	Output: HDCP 1.4 / 2.2; Input: HDCP 1.4
Audio	3.5 mm analog IN + OUT
LAN	2× RJ45, 1000 Mbps; LAN2 PoE
USB	2× USB 3.0 Type-A; 1× USB 2.0 Type-A; 1× USB-C
Wireless	IEEE 802.11 a/b/g/n/ac/ax; Bluetooth 5.2
Frequency	2.4 GHz & 5 GHz
Wi-Fi Rate	Up to 1200 Mbps
Connections	Up to 16 simultaneous connections
Windows	Up to 4 main + 12 thumbnails
Latency	<100 ms; minimum 20 ms
Power	12V DC / 3A; PoE via LAN2
Base Unit	190.60 × 110.20 × 25.60 mm
Control	RS-232; Web GUI; Telnet

Important: The uploaded manual does not contain a higher-resolution photographic product image than the embedded 1051×1279 image. This version therefore preserves that original image rather than inventing or modifying product details.