

MP-SUH4ARC-4K

HDMI 2.0 4x1 Switcher



KEY FEATURES

- 4 HDMI inputs to 1 HDMI output
- Up to 4K×2K@60Hz 4:4:4 HDR
- 18Gbps bandwidth
- HDMI 2.0 / HDCP 2.2 compliant
- ARC on HDMI Input 4
- Analog audio de-embedding
- Preset & user-defined EDID
- Auto/manual switching
- RS232, IR and CEC control
- Firmware upgrade via Micro-USB

TECHNICAL SPECIFICATIONS

Input	4 × HDMI, female Type-A	Output	1 × HDMI, female Type-A
Input Resolution	Up to 4K×2K@60Hz 4:4:4	Output Resolution	Up to 4K×2K@60Hz 4:4:4
HDMI Standard	2.0	HDCP Version	2.2
Audio Output	1 × 3.5mm stereo jack	Audio Format	PCM
Audio Impedance	70 Ohms	Frequency Response	20Hz–20kHz, ±3dB

GENERAL

Control	IR IN + RS232	Bandwidth	18Gbps
Power Supply	100–240V AC / 5V DC 1A	Power Consumption	5W Max.
Dimensions	194 × 15 × 81 mm	Net Weight	324g
Operating Temp.	–10°C to +55°C	Storage Temp.	–25°C to +70°C
Relative Humidity	10%–90%	ARC	HDMI Input 4

PACKAGE CONTENTS

1 × Switcher • 2 × Mounting Ears • 4 × Mounting Screws • 4 × Plastic Cushions • 1 × RS232 Cable (3.5mm to DB9) • 1 × IR Remote • 1 × IR Receiver • 1 × 5V DC 1A Power Adapter • 1 × User Manual

Product images are tightly cropped from the supplied MP-SUH4ARC-4K manual; specifications are taken from the same manual.